

12.1-RIM-3S2-R = 7' CENTER + (2) SQUARED ENDS

QTY	DESCRIPTION	PART NUMBER	VOLTAGE	PHASE	AMPS	TOTAL AMPS
4	23" LED 3500K, FROSTED, 24V	LG-FX-XXX-X	115V	1	0.04	0.16
2	29" LED 3500K, FROSTED, 24V	LG-FX-XXX-X	115V	1	0.05	0.10
6	34" LED 3500K, FROSTED, 24V	LG-FX-XXX-X	115V	1	0.07	0.42
4	45" LED 3500K, FROSTED, 24V	LG-FX-XXX-X	115V	1	0.09	0.36
2	56" LED 3500K, FROSTED, 24V	LG-FX-XXX-X	115V	1	0.11	0.22
10	EVAPORATOR FAN	RF-FA-XXXX	115V	1	0.17	1.70

CIRCUIT#1 (LIGHTS) TOTAL AMPS:1.26 VOLTAGE:115/1/60 CONNECTION:HARDWIRED
 CIRCUIT#2 (FANS) TOTAL AMPS:1.70 VOLTAGE:115/1/60 CONNECTION:HARDWIRED
 MODEL:RIM-3S APPLICATION:DELI BTUH:22675 EVAP TEMP: 22°F
 DEFROST: TIME-OFF, 4/40MIN, 47° TEMP TERMINATION
 SHIPPING DIMENSIONS: 158" X 82" X 67"
 WEIGHT: 2500 LBS

PACKOUT VOLUME: 66.76 CUBIC FT.
 INTERNAL VOLUME: 94.89 CUBIC FT.

CONFORMS TO UL STD 471.
 CONFORMS TO NSF STD 7.
 CERTIFIED TO CAN/CSA STD C22.2 NO. 120.

