

Project Name	
Model #	

Ρ

Approval _

__ Item # __

AIA# _

__ Qty ____

Gila Open Display Case | Cold ODC-03S-S & ODC-TS-S



SIS#



southerncasearts.com 800.552.6283

OVERVIEW

The Gila Open Display Case from Southern CaseArts

provides endless merchandise opportunities for grab-n-go foods and beverages. This self-contained case is available in 2 ft., 4 ft. and 6 ft. lengths, all with casters for maximum placement flexibility in your store. Whether you chose the TS model featuring a single wire rack or the 03S model which features two adjustable shelves, customers will love the ease of this open display case when looking for their favorite snacks, sandwiches, deli meats, cheese or beverages.


STANDARD FEATURES

- Nominal Length: 2.0', 4.0' & 6.0'
- Self-contained
- Shelving:

03S features 2 adjustable shelves with LED lights TS features a single wire rack for merchandise

• Exterior: Black powder coat

PRODUCT CATEGORIES





Dairv




Sandwiches



Chilled Beverages

Prepared Food



Plan Mechanical View

02.0-ODC-TS-S | Gila Open Display Case

QTY	DESCRIPTION	PART NUMBER	VOLTAGE	PHASE	AMPS	TOTAL AMPS
1	23" LED 3500K, FROSTED, 24V	LG-FX-XXX-X	115V	1	0.04	0.04
1	EVAPORATOR FAN	RF-FA-XXX-X	115V	1	0.17	0.17
1	CONDENSATE EVAP PAN / 800W / HALF	EL-EV-XXXX	115V	1	6.90	6.90
1	CONDENSING UNIT	RF-CU-0499-A	115V	1	8.30	8.30
CIRCUI	T#1 TOTAL AMPS: 15.41	VOLTAG	E: 115/1/60 PACKC			OP ANGLE CUBIC FT.

* OPTIONAL COMPONENT LOAD INCLUDED



southerncasearts.com


© 2024 Southern CaseArts. All rights reserved. Information and specifications subject to change without notice All values are design or typical values when measured under laboratory conditions

INTERNAL VOLUME: 6.32 CUBIC FT.



04.0-ODC-TS-S | Gila Open Display Case

QTY	DESCRIPTION	PART NUMBER	VOLTAGE	PHASE	AMPS	TOTAL AMPS
1	45" LED 3500K, FROSTED, 24V	LG-FX-XXX-X	115V	1	0.09	0.09
2	EVAPORATOR FAN	RF-FA-XXX-X	115V	1	0.17	0.34
1	CONDENSATE EVAP PAN / 800W / HALF	EL-EV-XXXX	115V	1	6.90	6.90
1	CONDENSING UNIT	RF-CU-0375-A	115V	1	8.24	8.24
CIRCUI	T#1 TOTAL AMPS: 15.57	VOLTAG	E: 115/1/60			ON: L5-20P



50春" [4'-2春"]-

* OPTIONAL COMPONENT LOAD INCLUDED


UME: 6.14 CUBIC INTERNAL VOLUME: 12.65 CUBIC FT.

Plan Mechanical View

06.0-ODC-TS-S | Gila Open Display Case

QTY	DESCRIPTION	PART NUMBER	VOLTAGE	PHASE	AMPS	TOTAL AMPS
1	67" LED 3500K, FROSTED, 24V	LG-FX-XXX-X	115V	1	0.13	0.13
3	EVAPORATOR FAN	RF-FA-XXX-X	115V	1	0.17	0.51
1	CONDENSATE EVAP PAN / 800W / FULL	EL-EV-XXXX	115V	1	6.67	6.67
1	CONDENSING UNIT	RF-CU-0381-A	115V	1	11.80	11.80
CIRCUI	T#1 TOTAL AMPS: 19.11	VOLTAG	E: 115/1/60	СС	NNECTIC	DN: L5-30P

VOLTAGE: 115/1/60 CONNECTION: L5-30P PACKOUT VOLUME: 9.21 CUBIC FT. INTERNAL VOLUME: 18.97 CUBIC FT.




Plan Mechanical View

* OPTIONAL COMPONENT LOAD INCLUDED

04.0-ODC-03S-S | Gila Open Display Case

QTY	DESCRIPTION	PART NUMBER	VOLTAGE	PHASE	AMPS	TOTAL AMPS
3	45" LED 3500K, FROSTED, 24V	LG-FX-XXX-X	115V	1	0.09	0.27
2	EVAPORATOR FAN	RF-FA-XXX-X	115V	1	0.17	0.34
1	CONDENSATE EVAP PAN / 800W / HALF	EL-EV-XXXX	115V	1	6.90	6.90
1	CONDENSING UNIT	RF-CU-0480-A	115V	1	10.90	10.90
CIRCUI	T#1 TOTAL AMPS: 18.41	VOLTAG	E: 115/1/60	СС	ONNECTIO	DN: L5-30P

PACKOUT VOLUME: 13.44 CUBIC FT. INTERNAL VOLUME: 21.22 CUBIC FT.



* OPTIONAL COMPONENT LOAD INCLUDED

06.0-ODC-03S-S | Gila Open Display Case

QTY	DESCRIPTION	PART NUMBER	VOLTAGE	PHASE	AMPS	TOTAL AMPS
3	67" LED 3500K, FROSTED, 24V	LG-FX-XXX-X	115V	1	0.13	0.39
3	EVAPORATOR FAN	RF-FA-XXX-X	115V	1	0.17	0.51
1	CONDENSATE EVAP PAN / 1200W / FULL	EL-EV-XXXX	115V	1	10.00	10.00
1	CONDENSING UNIT	RF-CU-0247	115V	1	11.70	11.70
CIRCUI	T#1 TOTAL AMPS: 22.60	VOLTAG	E: 115/1/60 PACKO			DN: L5-30P CUBIC FT.

INTERNAL VOLUME: 31.82 CUBIC FT.

74 5 [6'-2 5] INSIDE FRAME 8 KICK PLATE EVAP CUSTOMER SIDE - 51 5.]-

Plan Mechanical View

* OPTIONAL COMPONENT LOAD INCLUDED




southerncasearts.com

© 2024 Southern CaseArts. All rights reserved. Information and specifications subject to change without notice. All values are design or typical values when measured under laboratory conditions.



CONFORMS TO UL STD 471. CONFORMS TO NSF STD 7. CERTIFIED TO CAN/CSA STD C22.2 NO. 120.



02.0 Section View - TS-S

45<u>1</u>" [3'-9<u>1</u>"]

311

04.0 Section View - TS-S

45¹/₂" [3'-9¹/₂"]-

311

06.0 Section View - TS-S

--81/4"

က်ဖ

10,1

ADJUSTABLE

*OPTIONAL

(1) ROW OF

BUMPER

ADJUSTABLE

*OPTIONAL

(1) ROW OF

BUMPER

WIRE BASE

37<u>4</u>"

 $25\frac{7}{8}$

WIRE BASE

 $37\frac{1}{4}$ "

 $25\frac{7}{8}$

iD

INTAKE

Б

INTAKE

-8<u>1</u>"

00

10

EXHAUST

 $13\frac{3}{8}$ [3'-7 $\frac{3}{8}$ "].

*OPTIONAL

*OPTIONAL

CANOPY


LIGHT

EXHAUST


 $[3'-7\frac{3}{8}"]$ -

بيا هاي CANOPY

LIGHT



04.0 Section View - 03S-S



06.0 Section View - 03S-S

For more information on the Gila Open Display Case, contact one of our **Southern CaseArts** representatives or check out our website to learn more about all of the products offered by **Southern CaseArts**.



southerncasearts.com

© 2024 Southern CaseArts. All rights reserved. Information and specifications subject to change without notice. All values are design or typical values when measured under laboratory conditions.